




## FANGXING CORRUGATED UPVC ROOF TILE

### INTRODUCTION:




Fangxing Corrugated UPVC Roof Tile is a innovation of tri-ply co-extruded compound plastic with prominent quality, perfect resistance to fungus & humidity, recycable & colorfast.

### SPECIFICATIONS:




#### 720-W

Thickness: 1.0 mm, 1.2 mm, 1.5 mm,  
2.0 mm, 3.0mm.  
Width: 720 mm  
Length: accordingly  
Color: blue, white



#### 780-T

Thickness: 1.0 mm, 1.2 mm, 1.5mm,  
2.0mm, 3.0mm.  
Width: 780 mm  
Length: accordingly  
Color: blue, white



#### 940-T

Thickness: 2.0 mm, 3.0 mm.  
Width: 720 mm  
Length: accordingly  
Color: blue, white

### FITTINGS AND ACCESSORIES:



FITTINGS





## FANGXING CORRUGATED UPVC ROOF TILE

### FEATURES:



★ Prominent weather resistance



★ Excellent anti-load performance



★ Eximious anti-corrosion performance



★ Environment-friendly



★ Fire-resistance as Class B1



★ Convenient to install

### APPLICATIONS:

Fangxing Corrugated UPVC Roof Tiles have been widely used in the workshops, warehouse etc. The prominent anti-corrosion performance of Corrugated UPVC Roof Tiles is suitable for the applications in coastal areas with serious salt fog corrosion, and the areas with serious air pollution, especially in chemical industrial zone, etc.



### FANGXING BUILDING MATERIALS (SHANDONG) CO.,LTD

TEL: 86-532-85030055

FAX: 86-532-85039203

E-MAIL: EXPORT@FANGXING.COM

WEBSITE: WWW.FANGXING.COM

HEADQUARTER: ROOM A-3307, TOP YIHE INTERNATIONAL, NO.10

HONGKONG MIDDLE ROAD, QINGDAO 266071, CHINA.

PLANT: NO.668 BEIYUAN ROAD, LAIZHOU 261400, SHANDONG, CHINA